


Item			
Model	RX180-B	RX180	RX250
Picture			
Type	4x2	4x2	4x2
Rated Traction Force (kN)	3.7	3.7	5.7
Power of PTO Shaft(kW)	11.3	11.25	15.62
Engine	Brand: DE LI	Brand: JIAN XIANG	Brand: JIANG DONG
	Model: DLH1105	Model: TY290	Model: TY2100IT
	Type: 4 stroke, Vertical type,water-cooling, single cylinder	Type: 4 stroke, Vertical type,water-cooling, dual cylinder	Type: 4 stroke, Vertical type,water-cooling, dual cylinder
	Nominal Power (kW): 13.2	Nominal Power (kW): 13.2	Nominal Power (kW): 18.38
	Rated Speed (r/min): 2400	Rated Speed (r/min): 2200	Rated Speed (r/min): 2300
	Displacement(L): 0.996	Displacement(L): 1.272	Displacement(L): 1.65
Gearbox	6F+2R	6F+2R	8F+2R
Overall Dimensions(L×W×H) (mm)	2600×1180×1690	2900×1190×1750	2870×1300×1900
Wheelbase (mm)	1380	1440	1512
Front Wheel Tread (mm)	960	960	965
Rear Wheel Tread (mm)	980	980	950-1130
mm: Ground Clearance (mm)	250	300	320
Weight (Kg)	760	815	950
PTO Shaft Speed (r/min)	540	540	720
tire	4.00-14/7.50-20	4.00-14/7.50-20	5.00-16/9.5-24
Speed(Km/h)	29.37	30.20	29.41
Loading Quantity (units)	30 *	30 *	18 *
Optional	Front ballast	Front ballast	Front ballast
	Rear ballast	Rear ballast	Rear ballast
	ROPS/ROPS+Canopy	ROPS/ROPS+Canopy	ROPS/ROPS+Canopy
	Double Hydraulic Output	Double Hydraulic Output	Double Hydraulic Output
	PTO 540/1000	PTO 540/1000	PTO 540/1000

P.S. \* represents quantity for 40 GP; ▲ represents quantity for 40 HQ.

**TRACTORS**

<b>RX254</b>	<b>RX300</b>	<b>RX304</b>
		
4x4	4x2	4x4
6.5	5.9	7.4
17.48	18.75	20.96
Brand: JIANG DONG	Brand: JIANG DONG	Brand: JIANG DONG
Model: TY2100IT	Model: JD2102T	Model: JD2102T
Type: 4 stroke, Vertical type,water-cooling, dual cylinder	Type: 4 stroke, Vertical type,water-cooling, dual cylinder	Type: 4 stroke, Vertical type,water-cooling, dual cylinder
Nominal Power (kW): 18.38	Nominal Power (kW): 22.06	Nominal Power (kW): 22.06
Rated Speed (r/min): 2300	Rated Speed (r/min): 2400	Rated Speed (r/min): 2400
Displacement(L): 1.65	Displacement(L): 1.72	Displacement(L): 1.72
8F+2R	8F+2R	8F+2R
2988×1300×1900	2870×1300×1900	2988×1300×1900
1512	1550	1520
fixed 1000 or 970,1200,1300 optional	965	fixed 1000 or 970,1200,1300 optional
1000,1100,1200,1300 optional	950-1130	1000,1100,1200,1300 optional
318	320	318
1150	1060	1150
720	720	720
6.00-16/9.50-24	5.00-16/9.50-24	6.00-16/9.50-24
32.04	30.88	31.37
16 *	16 *	16 *
Front ballast	Front ballast	Front ballast
Rear ballast	Rear ballast	Rear ballast
ROPS/ROPS+Canopy	ROPS/ROPS+Canopy	ROPS/ROPS+Canopy/Cabin
Double Hydraulic Output	Double Hydraulic Output	Double Hydraulic Output
PTO 540/1000	PTO 540/1000	PTO 540/1000

<b>RX350</b>	<b>RX354</b>
	
4x2	4x4
5.9	8.3
21.8	24.47
Brand: LAI DONG	Brand: LAI DONG
Model: 4L22BT	Model: 4L22BT
Type: 4 stroke, Vertical type,water-cooling, 4 cylinder	Type: 4 stroke, Vertical type,water-cooling, 4 cylinder
Nominal Power (kW): 25.80	Nominal Power (kW): 25.80
Rated Speed (r/min): 2350	Rated Speed (r/min): 2350
Displacement(L): 2.16	Displacement(L): 2.16
8F+2R	8F+2R
3500×1300×1900	2780×1440×1430 ( without suspension)
1720	1606
965	fixed 1000 or 970,1200,1300 optional
950-1130	1000,1100,1200,1300 optional
318	318
1080	1180
720	720
5.00-16/9.50-24	6.00-16/9.50-24
33.54	27.55
8 *	8 *